

TRUCK 7



**MATERIAL
HANDLING**

Bulk tank truck discharge



APPLICATIONS

Delivery hose to transfer abrasive material such as cement, sand, etc.

TECHNICAL DESCRIPTION


Inner tube: natural rubber, black, smooth.

Reinforcement: synthetic textile and antistatic wire.

Cover: synthetic SBR rubber, black, fabric impression.

Temperature range: -30°C to +80°C.

Electrical properties: Conductive tube.
ATEX and TRGS 727 approval for hazardous areas.



**MATERIAL HANDLING****TRUCK 7**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
75.0	93.0 ±1.2	7	21	2.77	40	5513666	1
90.0	101.0 ±1.2	7	21	2	40	5513795	1
90.0	106.0 ±1.2	7	21	2.89	40	5513667	1
100.0	120.0 ±1.2	7	21	4.08	40	5513668	480
102.0	119.0 ±1.2	7	21	3	40	5513713	1
102.0	122.0 ±1.2	7	21	4	40	5513714	1
110.0	123.0 ±1.2	7	21	3	40	5513796	1
127.0	145.0 ±1.2	7	21	4.49	40	5513669	1
152.0	172.0 ±1.2	7	21	5.61	40	5513670	40

Tolerance on length: ±1% (ISO 1307 Standard).

**TRELLEBORG**