

ALIKLER D



PROCESSING EQUIPMENT

Food industry
Transfer



APPLICATIONS

High pressure discharge of liquid foodstuffs such as milk, beer, oil, fat, wine, cider, fruit juice and alcohol up to 95%.

Suction on unloading bays in dairies.

Equipment of processing and filling plants and liquid foodstuff tankers.

ADVANTAGES

- ┆ Smooth, seamless, white, multipurpose food grade tube that does not propagate bacterial growth.
- ┆ Able to recover its shape after accidental squeeze.
- ┆ Changes in temperature have little effect due to the qualities of the rubber compound.
- ┆ Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 130 °C.
- ┆ Non-marking, abrasion resistant cover.
- ┆ Contains no phthalate.

TECHNICAL DESCRIPTION

Inner tube: food grade oil resistant NBR, white, smooth.

Reinforcement: synthetic textile with embedded PET helix for ID≥50mm.

Cover: oil and weather resistant NBR/PVC, blue, fabric impression.

Temperature range: -30 °C to +100 °C.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.



FDA regulation No. 21 CFR 177.2600.



German legislation: BfR recommendation XXI cat. 2.



French legislation.



All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.

COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

RG

ALIKLER D



FDA



Made in France




TRELLEBORG

ALIKLER D



FDA



**PROCESSING EQUIPMENT****ALIKLER D**

ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	MAX. LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
32.0 -0/+1	44.0 ±1.5	15	40	0.7	220	1	20	0061567	ı
32.0 -0/+1	44.0 ±1.5	15	40	0.7	220	1	40	0061568	ı
38.0 -0/+1	51.0 ±1.5	15	40	0.7	265	1.2	20	0061569	ı
38.0 -0/+1	51.0 ±1.5	15	40	0.7	265	1.2	40	0061570	ı
50.0 -0/+1	66.0 ±1.5	15	40	0.7	210	1.97	20	0061571	ı
50.0 -0/+1	66.0 ±1.5	15	40	0.7	210	1.97	40	0061572	ı
63.0 -0/+1	79.0 ±1.5	15	40	0.7	270	2.38	20	0061573	ı
63.0 -0/+1	79.0 ±1.5	15	40	0.7	270	2.38	40	0061574	ı
75.0 -0/+1	91.0 ±1.5	15	40	0.7	290	2.85	20	0061575	ı
75.0 -0/+1	91.0 ±1.5	15	40	0.7	290	2.85	40	0061576	ı
76.0 -0/+1	92.0 ±1.5	15	40	0.7	300	3.22		5603141	ı
100.0 -0/+1	117.0 ±1.5	15	40	0.7	500	3.81	20	0061577	ı
100.0 -0/+1	117.0 ±1.5	15	40	0.7	500	3.81	40	0061578	ı

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

