

ALIKLER G2



PROCESSING EQUIPMENT

Food industry
Transfer



APPLICATIONS

Suction and discharge of liquid foodstuffs such as wine, beer, milk, oil, fats, cider, fruit juice and alcohol up to 95%.

For unloading bays, processing and filling plants and liquid foodstuff tankers.

Additional air line on road tankers carrying bulk powdered products (not compressor line) at temperatures up to +120 °C.

ADVANTAGES

- ┆ Improved flexibility, very easy to handle.
- ┆ A smooth, seamless, white, multipurpose food grade tube that does not propagate bacterial growth.
- ┆ Excellent resistance to kinking.
- ┆ Changes in temperature have little effect due to the qualities of the rubber compound.
- ┆ Resistant to cleaning with most common detergents (see our cleaning guideline for details) or with steam at max. 130 °C.
- ┆ Non-marking, abrasion-resistant cover.
- ┆ Contains no phthalate.

TECHNICAL DESCRIPTION

Inner tube: food grade quality oil resistant NBR, white, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant NBR/PVC, blue, fabric impression.

Temperature range: -30 °C to +100 °C.

STANDARD/APPROVAL

EU regulations No. 1935/2004, 2023/2006.



FDA regulation No. 21 CFR 177.2600.



German legislation: BfR recommendation XXI cat. 2.



French legislation.



All relevant migrations tests (France and FDA) were performed by the French institute of Poitiers (IANESCO) and confirmed compliant.


COUPLINGS/FITTINGS

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

RG

ALIKLER





**PROCESSING EQUIPMENT****ALIKLER G2**

| ID mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | MAX. VACUUM bar | BENDING RADIUS mm | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
|-------------|------------|----------------------------|-----------------------------|-----------------------|-------------------------|----------------|-------------|-------------------|---------------------------------|
| 25.0 -0/+1 | 37.0 ±1.0 | 10 | 30 | 0.9 | 40 | 0.92 | 20 | 5513357 | 1 |
| 25.0 -0/+1 | 37.0 ±1.0 | 10 | 30 | 0.9 | 40 | 0.92 | 40 | 5513358 | 1 |
| 32.0 -0/+1 | 44.0 ±1.0 | 10 | 30 | 0.9 | 55 | 1.1 | 20 | 5513359 | 1 |
| 32.0 -0/+1 | 44.0 ±1.0 | 10 | 30 | 0.9 | 55 | 1.1 | 40 | 5513360 | 1 |
| 38.0 -0/+1 | 50.0 ±1.0 | 10 | 30 | 0.9 | 65 | 1.26 | 20 | 5513361 | 1 |
| 38.0 -0/+1 | 50.0 ±1.0 | 10 | 30 | 0.9 | 65 | 1.26 | 40 | 5513362 | 1 |
| 45.0 -0/+1 | 57.0 ±1.0 | 10 | 30 | 0.9 | 90 | 1.45 | 20 | 5513363 | 120 |
| 45.0 -0/+1 | 57.0 ±1.0 | 10 | 30 | 0.9 | 90 | 1.45 | 40 | 5513364 | 120 |
| 50.0 -0/+1 | 62.0 ±1.5 | 10 | 30 | 0.9 | 100 | 1.77 | 20 | 5513365 | 1 |
| 50.0 -0/+1 | 62.0 ±1.5 | 10 | 30 | 0.9 | 100 | 1.77 | 40 | 5513366 | 1 |
| 50.0 -0/+1 | 65.0 ±1.5 | 10 | 30 | 0.9 | 100 | 2.24 | 20 | 5513383 | 400 |
| 50.0 -0/+1 | 65.0 ±1.5 | 10 | 30 | 0.9 | 100 | 2.24 | 40 | 5513384 | 400 |
| 53.0 -0/+1 | 65.0 ±1.5 | 10 | 30 | 0.9 | 110 | 1.86 | 20 | 5513367 | 1 |
| 53.0 -0/+1 | 65.0 ±1.5 | 10 | 30 | 0.9 | 110 | 1.86 | 40 | 5513368 | 1 |
| 63.0 -0/+1 | 76.0 ±1.5 | 10 | 30 | 0.9 | 135 | 2.24 | 20 | 5513369 | 1 |
| 63.0 -0/+1 | 76.0 ±1.5 | 10 | 30 | 0.9 | 135 | 2.24 | 40 | 5513370 | 1 |
| 70.0 -0/+1 | 84.5 ±1.5 | 10 | 30 | 0.9 | 175 | 3.07 | 20 | 5513371 | 120 |
| 70.0 -0/+1 | 84.5 ±1.5 | 10 | 30 | 0.9 | 175 | 3.07 | 40 | 5513372 | 120 |
| 75.0 -0/+1 | 89.5 ±1.5 | 10 | 30 | 0.9 | 190 | 3.29 | 20 | 5513373 | 1 |
| 75.0 -0/+1 | 89.5 ±1.5 | 10 | 30 | 0.9 | 190 | 3.29 | 40 | 5513374 | 1 |
| 75.0 -0/+1 | 91.0 ±1.5 | 10 | 30 | 0.9 | 190 | 3.53 | 20 | 5513385 | 200 |
| 75.0 -0/+1 | 91.0 ±1.5 | 10 | 30 | 0.9 | 190 | 3.53 | 40 | 5513386 | 200 |
| 76.0 -0/+1 | 90.5 ±1.5 | 10 | 30 | 0.9 | 200 | 3.45 | 20 | 5513980 | ∞ |
| 76.0 -0/+1 | 90.5 ±1.5 | 10 | 30 | 0.9 | 200 | 3.45 | 40 | 5513981 | 1 |
| 89.0 -0/+1 | 104.5 ±1.5 | 10 | 30 | 0.9 | 275 | 3.89 | 20 | 5513375 | 80 |
| 89.0 -0/+1 | 104.5 ±1.5 | 10 | 30 | 0.9 | 275 | 3.89 | 40 | 5513376 | 80 |
| 100.0 -0/+1 | 115.5 ±1.5 | 10 | 30 | 0.9 | 400 | 4.4 | 20 | 5513377 | 1 |
| 100.0 -0/+1 | 115.5 ±1.5 | 10 | 30 | 0.9 | 400 | 4.4 | 40 | 5513378 | 1 |
| 125.0 -0/+1 | 145.5 ±2.0 | 10 | 30 | 0.9 | 600 | 6.74 | 10 | 5513379 | 1 |
| 125.0 -0/+1 | 145.5 ±2.0 | 10 | 30 | 0.9 | 600 | 6.74 | 20 | 5513380 | 1 |
| 150.0 -0/+1 | 171.5 ±2.0 | 10 | 30 | 0.9 | 700 | 8.35 | 10 | 5513381 | 1 |
| 150.0 -0/+1 | 171.5 ±2.0 | 10 | 30 | 0.9 | 700 | 8.35 | 20 | 5513382 | 1 |

Tolerance on length: ±1% (ISO 1307 Standard).

∞ Upon availability.

Digital version

**TRELLEBORG**